



SH230LUX



Developed on the basis of the previous control unit, SH230, this special version is equipped with an integrated courtesy light while maintaining the main features of the base version. Its semi-transparent box allow to use SH230LUX as an applique.

Thanks to a special setting of the DIP-SWITCH, it is possible to switch on the light without opening the shutter.



Possibility to customize the box with your logo: MOQ 50 pcs

Technical data:

- Power supply: 230Vac +/-10%
- Motor power: 1350W (1HP)
- Working time: adjustable from 0,5 min to 2 minutes.
- Pause time: adjustable to 3 minutes max.
- Courtesy light time: adjustable to 3 minutes max.
- Safety edge input: 8k2 ohm or NC contact
- Courtesy light output: 12 V
- Flashing light output: 12 V
- Codes combination: 72 millions
- Storable transmitters: 25
- Transmitters programming mode: self-learning
- Frequency: 433.92 Mhz
- Sensitivity: > 100dbm
- Antenna: integrated
- Operating temperature: -10°C, +70°C
- Application: standard 50 mt - dead man 10 mt

APE - 528 / 1230

SH230LUX - Control unit for motorized rolling shutters

APE - 528 / 1244

KIT - control unit for motorized rolling shutters SH230LUX + tx EGOHOME

integrated courtesy light

APE - 550 / 1155

EGOHOME - 4 ch. transmitter 433,92 Mhz