

SH230 MULTI



Compatible with most fixed code, rolling code and HCS radiocommands, working at 433,92 MHz and 868 MHz



This 230V rolling shutters control unit is designed to guarantee maximum reliability and ease of management.

Integrates a multifrequency radio receiver (433,92÷868.3 MHz) able to memorize fixed code radiocommands.


Possible functions: adjustable working time, programmable automatic closure, deadman function, only opening command and safety management (photocells, shutdown button).

The IP53 degree of protection and the thermoplastic casing make it suitable for installation in protected external environments.

- Power supply: 230 Vac $\pm 10\%$ (50 Hz)
- Motor exit: 230 Vac – max 800 W
- Flashing light exit: 230 Vac – max 40 W
- Service exit: 12 Vac
- Multi-frequency radio receiver 433,92÷868.3 MHz
- Memory capacity: up to 400 codes (MF/MFA version)
- Programmable working time: 3÷90 s
- Automatica programmable closing: max 240 s
- Box dimensions: 140×96×50 mm
- Degree of Protection: IP53
- Operating temperature: -10°C, +50°C

APE-152/3010

SH230 MULTI AUX



Compatible with most fixed code, rolling code and HCS radiocommands, working at 433,92 MHz and 868 MHz



The “AUX” version of this control unit, compared to the SH230 MULTI, is **equipped with a clean contact auxiliary reley (AUX)**, programmable in bistable mode, pulse mode or with second/minute timer, usable for courtesy lights or other devices.

Integrates a multifrequency radio receiver (433,92÷868,30 MHz) able to memorize fixed code radiocommands.

Possible functions: adjustable working time, programmable automatic closure, deadman function, only opening command and safety management (photocells, shutdown button).

The IP53 degree of protection and the thermoplastic casing make it suitable for installation in protected external environments

Same features as **SH230MULTI**
but with programmable AUX relay
(5A 250 Vac / 5A 28 Vdc)

APE-152/3011